


All heaters have Quartz Tube elements and 3 prong cord set. Six models, at two voltages, provide a wide range of heating capacities from 500 to 5700 watts (1711 to 19,488 BTU/HR). Apply heat only where needed. Convenient ceiling chain mounting and cord set allow custom heating of only the areas being used. No need to waste energy heating the entire room or building.

APPLICATIONS

Designed for supplemental indoor heating in residential and commercial areas; Laundry rooms, Work shops, Toll booths, Garages, Assembly areas, Loading and Shipping docks and Well houses.

For residential and light commercial applications with gold anodized aluminum enclosure and reflector.



PMRR11012 has switches for 500 or 1000 watt operation.


For commercial and industrial applications with Statuary Bronze painted steel enclosure and gold anodized reflector



File # E21609

SELECTION CHART

				DIMENSIONS			
CATALOG	VOLTS	WATTS	REFLECTIVE	HEIGHT	WIDTH	LENGTH	WT.
NUMBER			ANGLE	in. (mm)	in. (mm)	in. (mm)	lbs. (Kg)
PMRR41512	120	1500	60Sym	3.375 (86) 5.5 (140)	45 (1168)	9 (4.1)	
PMRR53024	240	3000			57 (1448)	11 (5.0)	





The versatility of these heaters is doubled... They can be mounted on the ceiling or they can be mounted on the optional cart and rolled to any location for maximum spot heating effect. Both heaters have switches for full or 50% operation.

For commercial and industrial applications with Statuary Bronze powder coated steel enclosure and gold anodized reflector:

SELECTION CHART

				DIMENSIONS			
CATALOG	VOLTS	WATTS	REFLECTIVE	HEIGHT	WIDTH	LENGTH	WT.
NUMBER			ANGLE	in. (mm)	in. (mm)	in. (mm)	lbs. (Kg)
PMRR22012	120	2000/1000	60Sym	3.75 (95)	11 (280)	25 (637)	12 (5.5)
PMRR35724	240	5700/2850		3.73 (33)	19 (484)	34 (866)	22 (10)

ROLL-AROUND CART ACCESSORY



HEATER CONTROLLERS

SINGLE PHASE INFRARED

(FOR METAL SHEATH HEATERS ONLY)





File # E21609

SELECTION CHART

CATALOG NUMBER	DESCRIPTION	WEIGHT
PMRRCART	Roll-around cart	11 lbs
	(use with PMRR22012	
	or PMRR35724	

SELECTION CHART

CATALOG NUMBER	KW	VOLTS	PHASE	AMPS	WEIGHT
1PHC1	1.7	120	1	14.6	2 lbs
1PHC2	3.5	240	1	14.6	2 lbs