

ST & PT

1-1/2" Wide




Strip and Ring




- Two Terminals, Centered (type ST)
- Two Terminals, One End (type PT)
- 5-1/2 - 23-3/4" Lengths
- 125 - 1,000 Watts
- 120 and 240 Volt
- 12 - 27 W/in²

Dimensions (type PT)



Dimensions (type ST)



Applications

Strip heaters are used for heat transfer by conduction or convection to heat liquids, air, gases and surfaces. See guidelines in the Strip Heater Overview section.

Specifications and Ordering Information

Dimensions (In.)			Watts	W/in ²	Model	120V		240V		Wt. (Lbs.)
A	B	D				Stock	PCN	Stock	PCN	
ST — Chrome Steel Sheath										
10-1/2	9-1/2	9	350	15	ST-1003	NS	133102	NS	133110	0.8
12	11	10-1/2	500	17	ST-1205	NS	133129	NS	133137	0.9
15-1/4	14-1/4	13-3/4	500	12	ST-1505	NS	133145	NS	133153	1.1
17-7/8	16-7/8	16-3/8	750	15	ST-1807	NS	133161	NS	133170	1.4
23-3/4	22-3/4	22-1/4	1,000	14	ST-2401	NS	133188	NS	133196	1.8
PT — Rust-Resisting Iron Sheath										
5-1/2	4-1/2	4	125	14	PT-512	S	131959	S	257017	0.4
6	5	4-1/2	150	14	PT-615	S	131967	S	131975	0.5
PT — Chrome Steel Sheath										
5-1/2	4-1/2	4	250	27	PT-502	S	132329	S	257025	0.4
6	5	4-1/2	300	27	PT-603	S	132337	S	132345	0.5

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, PCN, watts, volts and quantity.

Note — Chromalox can furnish type PT made-to-order lengths between 7-1/2 and 23-3/4". As an option, see type OT strip heaters.