
Immersion

ARMTI-2 Solution Water Applications



- 2" NPT Stainless Steel Screw Plug
- INCOLOY[®] Sheath Elements
- High Watt Density (46 51 W/In²)
- 2 15 kW
- Integral Thermostat (DPST)
- 240 and 480 Volt, Single Phase
- General Purpose Terminal Enclosure

E1 — Dimensions (Inches)





Specifications and Ordering Information

							T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/In ²	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN
E1 Ger	neral	Purpo	se									
	240 480	1 1	51 51	2 2	8 8	6 6	ARMTI-2205-3T2 ARMTI-2205-3T2	AS AS	187987 188023	ARMTI-2205-3T1 ARMTI-2205-3T1	AS AS	187995 188031
	240 480	1 1	51 51	2 2	9 9	7 7	ARMTI-2255T2 ARMTI-2255T2	AS NS	188066 188103	ARMTI-2255T1 ARMTI-2255T1	AS AS	188074 188111
	240 480	1 1	48 48	2 2	12 12	7 7	ARMTI-2305T2 ARMTI-2305T2	AS AS	188146 188189	ARMTI-2305T1 ARMTI-2305T1	AS AS	188154 188197
	240 480	1 1	47 47	2 2	17-1/2 17-1/2	7 7	ARMTI-2405T2 ARMTI-2405T2	AS AS	188226 188269	ARMTI-2405T1 ARMTI-2405T1	AS AS	188234 188277
	240 480	1	46 46	2 2	19-5/8 19-5/8	8 8	ARMTI-2505T2 ARMTI-2505T2	AS AS	188306 188349	ARMTI-2505T1 ARMTI-2505T1	AS AS	188314 188347
	240 480	1 1	46 46	2 2	25-1/16 25-1/16	8 8	ARMTI-2605T2 ARMTI-2605T2	AS AS	188381 188429	ARMTI-2605T1 ARMTI-2605T1	AS AS	188390 188437
	240 480	1 1	49 49	2 2	28-1/8 28-1/8	9 9	ARMTI-2705T2 ARMTI-2705T2	AS AS	188461 188509	ARMTI-2705T1 ARMTI-2705T1	AS AS	188470 188517
-	240 480	1 1	46 46	2 2	40-5/8 40-5/8	10 10	ARMTI-21005T2 ARMTI-21005T2	AS AS	188541 188584	ARMTI-21005T1 ARMTI-21005T1	AS AS	188550 188592
	240 480	1	46 46	2 2	47-5/8 47-5/8	11 11	ARMTI-21205T21 ARMTI-21205T2	AS AS	188621 188664	ARMTI-21205T1 ¹ ARMTI-21205T1	AS AS	188630 188672
	240 480	1	50 50	2	54 54	12 12	ARMTI-21505T21 ARMTI-21505T2	AS AS	188701 188744	ARMTI-21505T1 ¹ ARMTI-21505T1	AS AS	188710 188752

1. Not UL Listed or CSA Certified (Exceeds 48 Amps).

Phone: 225-273-2202

Represented By: Ross & Pethtel

Website